

2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Streaks 'N Tips Temporary Color Highlight Spray	DATE:	6/17/2004
	(All Shades)	REV.	NEW

Section 1. Material Identification and Information

Hazardous Ingredients:				
-	Component	CAS #	%	TOXICOLOGICAL DATA
	Isobutane	75-28-5	55.0%	ACGIH TLV/TWA: 800ppm OSHA PEL/TWA: 1000ppm
	Alcohol Denat.	64-17-5	43.0%	ACGIH TLV/TWA: 1000ppm OSHA PEL/TWA: 1000ppm

Section 2. Physical / Chemical Characteristics

Boiling Point: Vapor Pressure:	N/A Not Determined	Specific Gravity: (@ 25°C)	0.88 (before addition of propellant)
(mm Hg and Temperat	ure)	Melting Point:	N/A
Vapor Density:	Not Determined	Evaporation Rate:	N/A
(Air = 1)		Water Reactive:	N/A
Solubility in Water:	Glitters not soluble in water.	% Volatile:	Approx. 98%
Appearance:	Glittered, Spray Mist		

Section 3. Fire and Explosion Hazard Data

Flash Point and Method Used:	73⁰F (Tag Closed Cup)	
Flammability Classification:	Extremely Flammable	
Auto-Ignition Temperature:	N/A	
Flammability Limits in Air % by Volume:	LEL: N/A	
	UEL: N/A	
Extinguishe <mark>r Me</mark> dia:	CO ₂ , Foam, Dry Chemical, and Water Spray.	
Special Fire Fighting Procedures:	Fire should be fought from a safe distance. Firefighters should wear full	
	face, self-contained breathing apparatus and full protective clothing.	
Unusual Fire and Explosion Hazards:	Closed containers exposed to excessive heat may rupture. Do not crush or puncture containers.	

2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Streaks 'N Tips T (All Shades)	emporary Color Highlight S	oray DAT REV	
Section 4. Reactivity Hazard Data				
Stability:	☑ Stable	Unstable		
Conditions to Avoid: Incompatibility (Mate	-	[.] open flames, sparks, high heat (ents.	>100⁰F), or other sou	urces.
Hazardous Decompo				
•		toxic gases when involved in fire		
Hazardous Polymeriz	• •	0		
-	☐ May Occur	Will Not Occur		
Section 5. Health	Hazard Data			
Primary Routes of Er	ntry:			
,	☑ Inhalation	Skin Absorption	☑ Ingestion	Eye Contact
Carcinogen Listed In	:		-	
	□ NTP	IARC Monograph	🗖 OSHA	☑ Not Listed
Health Hazards:	Eye Contact:	Mild to moderate irritation.		
	Skin Contact:	Mild to moderate irritation. Pr localized redness or rash.	olonged or repeated	contact may cause
	Inhalation:	Vapor may cause irritation to	the upper respiratory	/ tract.
	Ingestion:	May cause gastrointestinal irr	itation.	
Medical Conditions (Generally Aggravate	d by Exposure:		
		tory and skin disorder.		
Emergency First Aid				
	Eye Contact:	Flush eyes with plenty of wate persists, seek medical attention		e flushing. If irritation
	Skin Contact:	Wash thoroughly with mild so medical attention.	ap and water. If irrita	ation persists, seek
	Inhalation:	Remove victim to fresh air at a attention.	once. If breathing is	difficult, seek medical
	Ingestion:	DO NOT INDUCE VOMITING physician immediately.	 Drink enough wate 	er to dilute. Consult


Section 6. Control and Protective Measures

Respiratory Protections (Specific Type):

None required, when used with adequate ventilation.

Ventilation to be Used:

Use adequate ventilation.



2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Streaks 'N Tips Temporary Color Highlight Spray	DATE:	6/17/2004
	(All Shades)	REV.	NEW

Other Protective Clothing and Equipment:

None required under normal conditions of use. When handling large quantities (e.g., > 1 gallon), wear protective eyeglasses, gloves, boot, and apron per OSHA regulations (29 CFR 1910.133).

Hygienic Work Practices:

Wash hand thoroughly after using this product and before eating, drinking, or smoking.

Section 7. Precautions for Safe Handling and Use / Leak Procedures

Steps to be Taken if Material is Spilled or Released:

Before cleaning any spill or leak, individuals in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., < 1 gallon) wear appropriate personal equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure sources of ignition. Remove spilled material and place to appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state, and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills \geq 1 gallon, deny entry to all unprotected individuals. Contain spill with inert material (e.g., sand or earth). Transfer product to containers for recovery or proper disposal. Remove contaminated clothing promptly and wash affected areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Waste Disposal Methods:

Dispose of in accordance with federal, state, or local regulations.

Precautions to be taken in Handling and Storing:

Keep away from excessive heat, open flame, and other possible source of ignition. Do not store in damaged or unmarked containers or storage devices.

For warehouse storage, pallets and cases should be placed to avoid damage or rupture from material handling equipment. With use, spray aerosol carefully and cap after each use.

Other Precautions and/or Special Hazards:

None

Section 8. Transportation Information

49 CFR (GND):	Consumer Commodity, ORM-D (< 1.0L)
IATA (AIR):	Consumer Commodity, ORM-D-Air (< 0.5L)
IMDG(OCN):	



2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Streaks 'N Tips Temporary Color Highlight Spray	DATE:	6/17/2004
	(All Shades)	REV.	NEW

Section 9. Other Information

Hazardaya Matarial I	dontification System:	
Hazardous Material I	dentification System:	
	Health Hazard:	0 (minimal acute or chronic exposure hazard)
		1 (slight acute or chronic exposure hazard)
		2 (moderate acute or significant chronic exposure)
		3 (severe acute exposure hazard; onetime overexposure can result in permanent injury and may be fatal)
		4 (extreme acute exposure hazard; onetime overexposure can be fatal)
	Flammability Hazard:	: 0 (minimal hazard)
		1 (materials that require substantial pre-heating before burning)
		2 (combustible liquids or solids; liquids with a flashpoint of 38-93°C [100-
		200°F])
		3 (flammable liquids with a flashpoint below 38°C [100°F])
		4 (flammable liquids with a flashpoint below 23°C [73°F])
	Reactivity Hazard:	0 (normally stable)
		1 (materials that can become unstable at elevated temperatures or that react slightly with water)
		2 (materials that are unstable but do not detonate when initiated or which can react violently with water)
		3 (materials that can detonate when initiated or which can react explosively with water)
		4 (materials that can detonate at normal temperatures or pressures)
PPE Rating C:		d Apron required for routine chemical use.
U U	50 / 5/5	